

OMNITRONIC DD-5220L Turntable bk

Direct drive DJ turntable "Ultra Torque" with switchable phono/line output

Art. No.: 10603003 GTIN: 4026397433920







The article is no longer in our assortment.

Features:

- Direct drive high-torque motor Quartz-controlled for highest speed precision
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control ±10 %, ±20 %, ±50 %
- Selectable quartz-controlled pitch lock
- Quick start
- Adjustable start/stop time
- 2 large start/pause buttons
- Reverse run
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing and adjustable feet
- Switchable phono/line output
- Extremely resonance-free due to optimally combined components
- Platter and motor are directly connected for highest stability
- Recessed connections for easy case mounting
- Delivery includes headshell, slipmat and RCA cable
- Dust cover and pick-up system optionally available
- Pitch range: ±10%, ±20%, ±50%
- Package contents
- 1 x device, 1 x power cord, 1 x turntable platter, 1 x felt mat, 1 x shellset, 1 x balance weights, 1 x plug (male), 1 x adapter, 1 x RCA cable, 1 x user manual

Logistic

EAN / GTIN: 4026397433920 Weight: 12,35 kg Length: 0.52 m Width: 0.42 m Heigth: 0.19 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

| • | |
|--------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 15,00 W |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with Euro plug |
| Frequency range: | 20 - 20000 Hz |
| Drive type: | Quarz-controlled direct drive Brushless DC motor |
| Drive: | Initial torque: 4,5 kg/cm Start time: 0.2 - 6 sec, adjustable Stop time: 0.2 - 6 sec, adjustable Speed change time: <1s 1kHz 5cm/sec |
| Wow and flutter: | <0,1 % WRMS |
| Rumble: | 60 dB DIN B |
| Speed: | 33 RPM; 45 RPM; 78 RPM forward/backward |
| Tone arm: | S-shape with Cardan''s suspension Length: 230 Tonearm heigh: 8 - 10.5mm adjustable Overhang: 15mm Stylus pressure: 0-4g, adjustable |
| Output level: | Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec Line 90-216 mV/ 1 kHz 5 cm/sec |
| Connections: | Output: line/phono via 1 x stereo RCA |
| Pitch range: | ±10%, ±20%, ±50% |
| Dimensions: | Width: 45 cm Depth: 35,3 cm Height: 15,6 cm |
| Weight: | 11,30 kg |
| Turntable platter | |
| Material: | Metal |
| Dimensions: | Diameter: Ø 33,2 cm |
| Weight: | 1,425 kg |
| | |