

OMNITRONIC AZX-215A 2-way top active 350W

Active speaker with 15" woofer, 1,75" driver, 300 W RMS LF, 50 W RMS HF

Art. No.: 11039034 GTIN: 4026397638875



List price: 474.81 €

incl. 19% VAT.

Features:

- 2-way bass-reflex enclosure with 38 cm woofer and 4.5 cm titanium driver
- Master control with 2-band EQ
- HF adjustment -4 dB, -2 dB, 0 dB
- Black metal grille with acoustic foam
- Rugged carrying handle
- With rigging points
- Application possibility: Standing; suspended; monitoring; on stand
- Dual flange
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental

Package contents

1 x compact cabinet speaker, 1 x user manual, 1 x power cord

Logistic EAN / GTIN:

EAN / GTIN: 4026397638875

Weight: 27,45 kg Length: 0.49 m Width: 0.49 m Heigth: 0.77 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	650 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Rated: 300W RMS LF Rated: 50W RMS HF
Frequency range:	50 - 20000 Hz

Sensitivity:	95 dB (1W/1m)
Attachment system:	Dual flange: Ø 35mm (0°/5°)
Flying points:	7 x M10 thread
Circuitry:	Class D Biamp
Controls:	Limiter
Status LED:	Limit, power, signal
Connections:	Input: 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)
	Output: line via 1 x 3-pin XLR
Input channels:	1 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial
Equalizer:	Master: 1 x 2-band tone control
Speaker:	Woofer 15" with ferrit magnet
	Voice coil lows 3"
	Voice coil compression tweeter highs 1,75"
Type of speaker:	Compact cabinet speaker
Carrying handle:	1 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 43 cm
	Depth: 43 cm
	Height: 73 cm
Weight:	25,45 kg