

OMNITRONIC PAS-151A MK4 Subwoofer, active, DSP

Active 15" PA bassreflex subwoofer, 1400 W

Art. No.: 11039561

GTIN: 4026397739190



List price: 712.81 €

incl. 19% VAT.

Features:

- Active PA subwoofer for touring applications and permanent installations
- XLR outputs with switchable high-pass filter, 120 Hz
- Digital signal processor
- DSP presets: FLAT; KICK; DEEP
- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- 4 wheels optional

Package contents

- 1 x bass, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397739190

Weight: 33,20 kg

Length: 0.60 m

Width: 0.62 m

Height: 0.55 m

Bulky product

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1100 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 8 A fuse replaceable
Power:	Program: 1400W Rated: 700W RMS
Frequency range:	38 - 200 Hz

Max. SPL:	128 dB
DSP:	Digital signal processor
DSP presets:	FLAT; KICK; DEEP
Cooling:	1 x cooling fan
Filter:	Hi cut: 120 Hz; hi cut: 100 Hz
Attachment system:	1x M20 thread
Circuitry:	Class D
Control elements:	Power switch, Master control, Phase reversal switch, tone control, crossover frequency
Controls:	Limiter; power on/off transients
Status LED:	Power, peak, DSP presets
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 2 x 3-pin XLR (M) mounting version
Speaker:	1 x woofer 15" with ferrit magnet Basket material: aluminum Conematerial: cardboard/paper Voice coil lows 4"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	2 pc/pcs
Transport aid:	4 x wheels optional
Grid size:	7,5 mm
Material:	Plywood multi-layer glued, 15 mm
Color:	Black
Dimensions:	Width: 55 cm Depth: 46,5 cm Height: 52 cm
Weight:	30,45 kg