

## RELACART UT-222 Bodypack 522-554 MHz with HM-600S Headset

Bodypack transmitter with PLL multifrequency transmitter

Art. No.: 13055183

GTIN: 4026397735215



**List price: 148.75 €**

incl. 19% VAT.

### Features:

- Durable aluminum alloy housing, applicable for touring
- Pilot frequency squelch technology delete wireless RF interference
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Adjustable input gain
- RF output power Hi/Low adjustable
- Lock function for prevents undesired changes to settings
- Up to 12 transmitters can be operated in parallel without interference

#### transmitter

- Operating range up to 80m
  - OLED display
- #### microphone
- Polar pattern: Omnidirectional
  - For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x transmitter, 1 x microphone, 1 x windshield, 1 x user manual, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397735215

Weight: 0,35 kg

Length: 0.29 m

Width: 0.12 m

Height: 0.07 m

### Technical specifications:

Parallel mode:	Max. 12 transmitter
Weight:	0,22 kg
Transmitter	
Type:	Bodypack with microphone
Power supply:	3V DC

Power connection:	Battery/battery pack
Battery:	2 x Mignon (AA) (not included)
Gain:	0 dB -6 dB -12 dB
Range:	Range up to 80m
Frequency band:	UHF 522 - 554 MHz
Switching bandwidth:	32 MHz
RF power output:	10 mW (LO); 30 mW (HI)
Modulation:	FM
Frequency selection:	151 switchable frequencies In 10 groups with up to 18 preset frequencies each
Display type:	OLED display
Control elements:	Transmitter power switch (high-low)
Connections:	Output: Mini XLR (M) 4-pin mounting version
Switch:	On/off/mute switch
Material:	Aluminum
Color:	Black
Dimensions:	Width: 6,6 cm Depth: 2,3 cm Height: 8,4 cm
Weight:	0,174 kg
<b>Microphone</b>	
Type:	Headset microphone
Power supply:	2-10V DC
Cable length:	1,2 m
Capsule type:	Condenser Size: Ø 5 mm x 6 mm
Polar pattern:	Omnidirectional
Frequency range:	50 - 18000 Hz
Sensitivity:	-47 dB
Impedance:	1800 Ohm
Connector type:	Mini XLR (F) 4-pin
Color:	Skin-colored
Weight:	0,028 kg