

---

## OMNITRONIC UHF E-FLEX 2, Wireless Mic System 823-832/863-865 MHz Art. No.: 13063370

License-free 2-channel microphone system (UHF 863 - 865 MHz, UHF 823 - 832 MHz) with auto sync, incl. rack fit GTIN: 4026397740226

---

**The article is no longer in our assortment.**

### Features:

- 2-channel receiver and 2 hand-held microphones with UHF PLL technology
  - Quick and easy frequency adjustment at handheld transmitter
  - 16 selectable UHF frequencies (823-832 and 863-865 MHz)
  - 2 separate channels with volume controls
  - Balanced XLR output per channel
  - 6.3 mm jack for mixed signal output
  - Detachable BNC antennas
  - Operating range up to 30m with line-of-sight
  - UHF 863 - 865 MHz License-free and approved in Europe
  - UHF 823 - 832 MHz License-free and approved in large parts of Europe
- receiver**
- Multicolor 4 digit 7-segment LED display
  - (19") 48.3 cm rack installation possible
- microphone**
- Polar pattern: Cardioid
  - 4 digit 7-segment LED display
- Package contents**
- 2 x microphone, 1 x receiver, 1 x external mains adapter, 2 x antenna, 1 x jack cable, 2 x mounting bracket, 4 x screw

### Logistic

EAN / GTIN: 4026397740226

### Technical specifications:

Type:	Wireless set
Range:	Range up to 30m with line-of-sight

Frequency band:	UHF 863 - 865 MHz; UHF 823 - 832 MHz
Modulation:	FM
Frequency selection:	16 switchable frequencies In 2 groups
Microphone	
Type:	Hand-held transmitter
Power supply:	3V DC
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	Mignon (AA) (not included)
Frequency range:	50 - 15000 Hz
RF power output:	10 mW
Housing color:	Black
Display type:	4 digit 7-segment LED display
Switch:	On/off/mute switch
Material:	Metal
Dimensions:	Length: 24,3 cm Diameter: Ø 5,5 cm
Weight:	0,27 kg
Receiver	
Power supply:	100-240 V AC, 50/60 Hz 12V DC 500 mA
Power consumption:	Max. 3,1 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) power supply cord with AC unit (provided)
Number of channels:	2
Frequency range:	50 - 15000 Hz
S/N ratio:	>90 dB
THD:	<0,05 % at 1 kHz
Housing color:	Black
Display type:	Multicolor 4 digit 7-segment LED display
Display:	Mute; channel , frequency , AF audio level , RF signal level
Control elements:	Power switch, level control per channel
Connections:	Input: antenna via 2 x BNC (F) Output: microphone via 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR (M) mounting version
Material:	Metal
Housing design:	(19") 48.3 cm rack installation possible
Mounting depth:	18,5 cm
Dimensions:	Width: 21,1 cm Depth: 14,4 cm Height: 4,2 cm
Weight:	0,970 kg