

# EUROLITE Set 4x AKKU UP-4 QCL Spot QuickDMX MK2 + Plastic case

Art. No.: 20001038

GTIN: 4026397710106







List price: 1605.31 €

incl. 19% VAT.

#### Features:

#### **EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2**

Bright battery powered LED uplight with 10 W 4in1 LEDs and QuickDMX

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- 4 powerful LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; Dimmer speed (step response) adjustable; color fade adjustable speed; color change adjustable speed; white balance adjustable; color blend adjustable; frost filter; color selection manual; program selection manual; pulse-width modulation; Energy-saving mode; Emergency lighting function in case of power failure
- Multi beam effect; spot effect; wash effect; strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM
- Up to 6 transmitters can be operated in parallel without interference
- DMX fail mode (blackout; hold; static; full on)
- With a beam angle of 7°
- With bracket for floor use
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; rental
- Silent operation
- Application possibility: Standing; suspended
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- With a KENSINGTON LOCK theft protection

### Logistic

EAN / GTIN: 4026397710106

Weight: 19,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

- Preprogrammed in Colorchief
- Flicker-free
- QuickDMX: operating range up to 600m in the open air
- Monochrome OLED display
- Display of the remaining battery life for the current setting
- Charge status indicator
- 3 buttons on the remote control for saving your own settings

#### Package contents

1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control,
1 x battery, 1 x frost filter, 1 x knurled screw

### ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

#### Carrying case

- With 4 device compartment
- High-quality workmanship with plastic, black
- Interior with foam padding<BR>cover with foam padding
- Rugged carrying handle
- 4 high-quality spring locks with shut-off function
- 4 plastic feet
- For application areas such as: Mobile use; rental; mobile djs / entertainer

#### Package contents

1 x case

### **Technical specifications:**

Weight: 15,62 kg

# EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

Power supply:	100-240 V AC, 50/60 Hz	
IP classification:	IP20	
Protection class:	Protection class I	
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)	
Cable construction:	3 x 1,0 mm² H05VV-F	
Power output:	P-Con (gray), mounting version	
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh	
Battery pack:	Battery operation up to 9h depending on program used	
	Recharging time 3h	
Lamp type:	LED lamp	
LED type:	4 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)	
Flash rate:	27 Hz	
DMX channels:	3; 4; 6; 8; 11	
DMX input:	3-pin XLR (M) mounting version	
DMX output:	3-pin XLR (F) mounting version	
Cooling:	Passive convection cooling	
Control:	IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM	

Preprogrammed in:	Colorchief	
Projection:	Flicker-free	
PWM frequency:	3000 Hz	
Range:	QuickDMX: range up to 600m in the open air	
Carrier frequency:	2,4 GHz	
Parallel mode:	Max. 6 transmitter	
Modulation:	GFSK	
DMX fail mode:	Blackout; hold; static; full on	
Beam angle:	7°	
Beam angle (1/2 peak):	7°	
	Frost filter 20°	
Beam angle (1/10 peak):	18°	
	Frost filter 42°	
Distance to wall:	500 mm	
Attachment system:	Bracket for floor use	
Display type:	Monochrome OLED display	
Display:	Battery runtime calculation , charge status indicator	
Material:	Metal, painted	
Theft protection:	KENSINGTON LOCK	
Dimensions:	Length: 15,4 cm	
	Width: 13,3 cm	
	Height: 15,8 cm	
Weight:	2,83 kg	
Noise classification:	Class 0 (no noise at all)	
Remote control		
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in	
Legal specifications		
Special product:	Not designed for household room illumination	
Intended use:	Show effect lighting	

# ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

Maximum load:	25 kg	
Carrying handle:	1 pc/pcs	
Lock:	Spring lock: 4 pc/pcs with shut-off function	
Transport aid:	4 x plastic feet	
Material:	Plastic	
Color:	Black	
Inside dimensions:	49 cm x 36 cm x 13 cm	
Device compartment:	16 cm x 13,5 cm x 16 cm	
Accessory compartment:	8 cm x 30,5 cm x 16 cm	
Dimensions:	Length: 55 cm	
	Depth: 42,5 cm	
	Height: 21 cm	

Veight:	4,30 kg	