

**The article is no longer in our assortment.**

### Features:

---

- 1 powerful LED 230 W COB (chip-on-board) 4in1 QCL RGBL (homogenous color mix)
  - Zoom motor driven
  - Dimmer; dimmer curves; color blend
  - Wash effect
  - The device is cooled by temperature-controlled fan
  - Control via stand-alone; DMX; QuickDMX via USB (optional); RDM; quick select potentiometer for brightness and Zoom
  - Flicker-free
  - With a beam angle of 3° - 56°
  - Variable color temperature 2400 K - 8500 K
  - Direct color temperature selection for 62 preset values
  - With mounting bracket
  - Monochrome LCD display
  - Mains input and output for power linking up to 8 units
  - Built with SEETRONIC connector
  - For application areas such as: Stage; theater; concerts/FoH's; video and photography
  - Very quiet working noise
  - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame, 1 x barndoor

### Logistic

---

EAN / GTIN: 4026397742770

### Technical specifications:

---

Power supply: 100-240 V AC, 50/60 Hz

---

Power consumption:	230 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1,5 mm <sup>2</sup> H05VV-F
Cable length:	1,75 m detachable
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 230 W COB (chip-on-board) 4in1 QCL RGBL (homogenous color mix)
Flash rate:	1 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	1; 2; 4; 7
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	1 x temperature-controlled fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); RDM; quick select potentiometer for brightness and Zoom
Projection:	Flicker-free
Beam angle:	3° - 56°
Beam angle (1/2 peak):	3 - 40°
Beam angle (1/10 peak):	13 - 56°
Color temperature:	2400K - 8500K adjustable
Lamp life:	30000 h
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome LCD display
USB port:	Type A
Diameter mounting holes:	3 x Ø10mm
Use of brands:	Built with SEETRONIC connector
Material:	Metal
Dimensions:	Length: 37,0 cm Width: 35,0 cm Height: 39,5 cm
Weight:	9,5 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments) depending on mode used
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting