

EUROLITE AKKU Slim Tube AIR Set

Art. No.: 41700400

4 battery-powered effect tubes with 32 pixels, AirW wireless system (2.4 GHz), remote control and bag

GTIN: 4026397739565

The article is no longer in our assortment.

Features:

- 4 pieces per set
- Cordless, flexible and versatile
- Integrated AirW radio transceiver for wireless master/slave operation
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- 32 powerful LEDs 0,25 W SMD 5050 3in1 TCL RGB
 LEDs controlled separately
- 40 integrated show programs
- Direct color selection for 20 preset colors
- Frost filter
- Dimmer electronic; Energy-saving mode adjustable; color macros preset; program selection manual; color blend stepless; color selection adjustable; color fade adjustable; running light adjustable; effect speed adjustable speed; pulse effect adjustable speed
- Strobe effect
- Control via stand-alone; DMX; AirW; wireless remote control; master/slave function; sound to light via microphone; QuickDMX via USB (optional)
- 3 buttons on the remote control for saving your own settings
- DMX fail mode (blackout; hold; full on)
- Battery operation up to 8h depending on program used
- Integrated automatic charging of the battery
- Charge status indicator
- Flicker-free
- 4 digit 7-segment LED display
- The device is cooled by passive convection cooling
- The article is delivered with practical transport bag
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

Logistic

EAN / GTIN: 4026397739565

- Application possibility: Standing; suspended
 - AirW: operating range up to 70m with line-of-sight
 - Preprogrammed in LED PC-Control 512
- remote control**
- Operating range up to 30m with line-of-sight
- Package contents**
- 4 x light effect, 4 x frost filter, 4 x stand, 1 x charger, 1 x remote control, 1 x battery, 1 x bag, 1 x user manual, 1 x declaration of conformity

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 5V DC 1400 mA
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter (provided)
Battery pack type:	1 x lithium ion 7,4 V, 2600 mAh, 19,24 Wh
Battery pack:	Battery operation up to 8h depending on program used Recharging time 5h
Lamp type:	LED lamp
LED type:	32 x 0,25 W SMD 5050 3in1 TCL RGB
Flash rate:	0,5 - 30 Hz
Equipment:	Frost filter
DMX channels:	4; 6; 10; 13; 19; 49
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; AirW; wireless remote control; master/slave function; sound to light via microphone; QuickDMX via USB (optional)
Preprogrammed in:	LED PC-Control 512
Projection:	Flicker-free
Range:	AirW: range up to 70m with line-of-sight
Carrier frequency:	2,4 GHz
DMX fail mode:	Blackout; hold; full on
Standing/fixation:	Stand
Beam angle (1/2 peak):	360°
Housing color:	Transparent
Attachment system:	1x Ø 10mm
Display type:	4 digit 7-segment LED display
Display:	Charge status indicator
Status LED:	Charge status indicator; signal
USB port:	1 x type C
Dimensions:	Length: 151 cm Width: 6 cm Height: 5 cm Diameter: Ø 3,25 cm

Weight:	3,8 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x 12 V 23AE alkaline manganese built-in
Range:	Range up to 30m with line-of-sight
Carrier frequency:	433,92 MHz
Bag	
Dimensions:	Length: 155 cm
	Width: 20 cm
	Height: 17 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting