eurolite®

EUROLITE Set 4x LED PARty Spot Silent RGB/WW with Soft Bag

Compact spotlight with 12 x 5 W 4in1 QCL RGB/WW LED and DMX control

Art. No.: 42110204 GTIN: 4026397724882











List price: 284.41 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change programs; Dimmer electronic
- Strobe effect
- 10 integrated show programs
- Direct color selection for 20 preset colors
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light'J; Light Captain; LED PC-Control 512
- Flicker-free
- The article is delivered with practical transport bag
- With a beam angle of 12°
- With double bracket
- 4 digit 7-segment LED display
- 4 pieces per set
- For application areas such as: Wedding/gala/events; party room; mobile djs / entertainer
- Silent operation
- Package contents
- 4 x device, 1 x user manual, 1 x remote control, 1 x battery, 1 x bag

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	17 W

Logistic

EAN / GTIN: 4026397724882 Weight: 2,90 kg Length: 0.41 m Width: 0.17 m Heigth: 0.21 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection: Fixed power supply cord with Euro plug Device fuse: T 1 A fuse fix in power supply Lamp type: LED lamp LED type: 12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) DMX channels: 4; 6; 8 DMX output: 3-pin XLR (M) mounting version Control: 3-pin XLR (F) mounting version Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional) Preprogrammed in: Light 'J; Light Captain; LED PC-Control 512 Projection: Flicker-free Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Diameter: 9 cm Wright: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter: Diameter mounting holes: 2 x Ø6m;; 1 x Ø13mm Baterial: Metal, 1,5 mm Legal specifications Special product:	IP classification:	IP20
Device fuse: T 1 A fuse fix in power supply Lamp type: LED lamp LED type: 12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) DMX channels: 4; 6; 8 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by Stand-alone; sound to ilght via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); CRMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by Stand-alone; sound to ilght via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); CRMX by Stand-alone; sound to use (optional); CRMX by LumenRadio via USB (optional); W-DMX by Stand-alone; Sound to USB (optional); W-DMX by Stand-alone; Sound to USB (optional); CRMX by LumenRadio via USB (optional); CRMX by Stand-alone; Sound to USB (optional); CRMX by Stand-alone; Sound to USB (optional); CRMX by Stand-alone; Sound to USB (optional); CRMX by Stand to USB (optional); CRMX by Stand-alone; Sound toptional; CRMX b	Protection class:	Protection class II
Lamp type: LED lamp LED type: 12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) DMX channels: 4; 6; 8 DMX output: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by LumenRadio via USB (optional); W-DMX by LumenRadio via USB (optional); W-DMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by LumenRadio via USB (optional); CRMX by LumenRadio	Power connection:	Fixed power supply cord with Euro plug
LED type: 12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) DMX channels: 4; 6; 8 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Preprogrammed in: Light 'J; Light Captain; LED PC-Control 512 Projection: Flicker-free Beam angle: 12° Beam angle (1/12 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Diameter: Ø 12,5 cm Height: 19 cm Diameter: Ø 12,6 cm Height: 19 cm Diameter: Ø 12,6 cm Vidth: 15,5 cm Height: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Legal specifications Special product:	Device fuse:	T 1 A fuse fix in power supply
RGB/WW (homogenous color mix)DMX channels:4; 6; 8DMX input:3-pin XLR (M) mounting versionDMX output:3-pin XLR (F) mounting versionControl:Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); W-DMX by uumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); Proportion:Preprogrammed in:Light 'J; Light Captain; LED PC-Control 512Projection:Flicker-freeBeam angle:12°Beam angle (1/2 peak):12°Beam angle (1/10 peak):30°Housing color:Black matteAttachment system:Double bracketDisplay type:4 digit 7-segment LED displayDimensions:Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cmWeight:2,60 kgNoise classification:Class 0 (no noise at all)Mounting bracketDiameter mounting holes:2 x Ø6mm; 1 x Ø13mm Material:Metal, 1,5 mm Legal specificationsSpecificationsSpecificationsSpecificationsSpecification milumination	Lamp type:	LED lamp
DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); VI-DMX by wireless solution via USB (optional); VI-DMX by LumenRadio via USB (optional); Preprogrammed in: Light 'J; Light Captain; LED PC-Control 512 Projection: Flicker-free Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter: Ø 12,5 cm Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product:	LED type:	
DMX output: 3-pin XLR (F) mounting version Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Preprogrammed in: Light'J; Light Captain; LED PC-Control 512 Projection: Flicker-free Beam angle: 12° Beam angle (1/2 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter: Ø 12,5 cm Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Legal specifications Secial product: Not designed for household room illumination Secial product:	DMX channels:	4; 6; 8
Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Preprogrammed in: Light'J; Light Captain; LED PC-Control 512 Projection: Flicker-free Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Not designed for household room illumination	DMX input:	3-pin XLR (M) mounting version
master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional) Preprogrammed in: Light'J; Light Captain; LED PC-Control 512 Projection: Flicker-free Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket 2 x Ø6mm; 1 x Ø13mm Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Legal specifications Not designed for household room illumination	DMX output:	3-pin XLR (F) mounting version
Projection: Flicker-free Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket 2 x Ø6mm; 1 x Ø13mm Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Legal specifications Special product:	Control:	master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by
Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Vidth: 15,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Not designed for household room illumination	Preprogrammed in:	Light'J; Light Captain; LED PC-Control 512
Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Not designed for household room illumination	Projection:	Flicker-free
Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket 2 x Ø6mm; 1 x Ø13mm Diameterial: Metal, 1,5 mm Legal specifications Special product:	Beam angle:	12°
Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination	Beam angle (1/2 peak):	12°
Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: Diameter in: Metal, 1,5 mm Legal specifications Not designed for household room illumination	Beam angle (1/10 peak):	30°
Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket 2 x Ø6mm; 1 x Ø13mm Diameterial: Metal, 1,5 mm Legal specifications Not designed for household room illumination	Housing color:	Black matte
Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product:	Attachment system:	Double bracket
Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product:	Display type:	4 digit 7-segment LED display
Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination	Dimensions:	Width: 15,5 cm Height: 19 cm
Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination	Weight:	2,60 kg
Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination	Mounting bracket	
Legal specifications Special product: Not designed for household room illumination	Diameter mounting holes:	2 x Ø6mm; 1 x Ø13mm
Special product: Not designed for household room illumination	Material:	Metal, 1,5 mm
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting