


EUROLITE PolarStar RGB Laser

Star laser for colored and white star effects and LED northern light effect

Art. No.: 51741069

GTIN: 4026397743647



The article is no longer in our assortment.

Features:

- 1 powerful LED 7 W SMD 3in1 TCL RGB
- With a beam angle of 23°
- Laser
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- 3 integrated show programs
- Animation wheel rotating
- Dimmer electronic
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- DMX fail mode (hold; blackout)
- 3 digit 7-segment LED display
- DMX feed-through for up to 32 further DMX devices
- Flicker-free
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- The device is cooled by passive convection cooling
- Very quiet working noise
- Application possibility: Suspended; on stand
- With mounting bracket

Package contents

- 1 x light effect, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397743647

Weight: 1,85 kg

Length: 0.30 m

Width: 0.25 m

Height: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Cable length:	1,4 m
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 7 W SMD 3in1 TCL RGB
Flash rate:	0,5 - 20 Hz
Equipment:	Animation wheel rotating
Laser class:	2M
Laser color:	R/G/B
Laser module:	R/G/B 193 mW
DMX channels:	8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Projection:	Flicker-free
PWM frequency:	23500 Hz
DMX features:	DMX feed-through for up to 32 further DMX devices
DMX fail mode:	Hold; blackout
Beam angle:	23°
Beam angle (1/2 peak):	23°
Housing color:	Black
Attachment system:	3x Ø 10mm Mounting bracket
Display type:	3 digit 7-segment LED display
USB port:	Type A
Material:	Aluminum
Dimensions:	Width: 24,0 cm Depth: 20,5 cm Height: 16,5 cm
Weight:	1,62 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)