

LASERWORLD PL-20.000RGB IP65


Diode showlaser with ShowNET network interface and free software

Art. No.: 51743324 GTIN: 7640144997922









incl. 19% VAT.

Features:

- Full color mixing laser with analog color modulation
- Integrated show programs
- Control via ILDA; DMX; stand-alone; Art-Net; master/slave function
- For application areas such as: Installation; stage; rental; architecture
- With mounting bracket
- Application possibility: Suspended
- Suitable for outdoor use IP65

Package contents

- 1 x laser, 1 x user manual, 1 x power cord, 1 x case, 2 x key

Logistic

EAN / GTIN: 7640144997922

Weight: 54,00 kg Length: 0.69 m Width: 0.59 m Heigth: 0.40 m Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	750 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Laser class:	4
Laser color:	R/G/B

Laser module:	Red (R) 6000 mW 638nm
	Green (G) 8000 mW 520nm
	Blue (B) 8000 mW 450nm
DMX input:	1 x 5-pin XLR (F) mounting version IP
DMX output:	1 x 5-pin XLR (M) mounting version IP
Control:	ILDA; DMX; stand-alone; Art-Net; master/slave function
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 42,7 cm
	Width: 28,0 cm
	Height: 22,0 cm
Weight:	26,00 kg
Noise classification:	Class 2 (slight noise)