

EUROLITE LED TMH-13 Moving Head Spot

Compact moving head Spot with 10 W LED, gobos and color wheel

Art. No.: 51785972

GTIN: 4026397693508



The article is no longer in our assortment.

Features:

- Compact lightweight
- 1 powerful LED 10 W high-power
- Positioning within 540° PAN, 200° TILT
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; focus manual
- Gobo effect; beam effect; strobe effect
- Color wheel with 7 dichroic filters plus open half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 13°
- 4 digit 7-segment LED display
- Dimmer electronic
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet, 2 x screw

Logistic

EAN / GTIN: 4026397693508

Weight: 3,08 kg

Length: 0.28 m

Width: 0.22 m

Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 10 W high-power
Max. TILT movement:	200° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Equipment:	Gobo wheel with static gobos; focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 7 gobos and open
DMX channels:	9; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	13°
Beam angle (1/2 peak):	13°
Illuminance in Lux (lx):	Cold white (CW) 3m: 342 lx, 6m: 86 lx
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 16 cm Depth: 15,8 cm Height: 28 cm
Weight:	2,61 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting