eurolite®

EUROLITE LED PST-12W 3000K Spot

Narrow beam pinspot with 12 W warm white (WW) LED



Art. No.: 51916110 GTIN: 4026397735956









List price: 47.48 €

incl. 19% VAT.

Features:

- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- For application areas such as: Trade fair and shop fitting; installation; restaurants, bars and hotels; video and photography
- Very high color rendering index (CRI)
- 1 powerful LED 12 W COB (chip-on-board) warm white (WW)
- Focus manual; zoom manual
- Spot effect
- The device is cooled by passive convection cooling
- Control via plug and play
- Silent operation
- Application possibility: Suspended; on stand; wall mounting **Package contents**
- 1 x spotlight, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	12 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug built-in
Lamp type:	LED lamp

Logistic

EAN / GTIN: 4026397735956 Weight: 0,50 kg Length: 0.19 m Width: 0.18 m Heigth: 0.08 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

LED type:	1 x 12 W COB (chip-on-board) warm white (WW)
Equipment:	Focus manual; zoom manual
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	12° monochrome
	11° monochrome
	10° monochrome
	7° monochrome
Beam angle (1/10 peak):	16°
	14°
	12°
	9°
Color temperature:	3000K
Color rendering index (CRI):	97 Ra
Illuminance in Lux (lx):	1m: 3308 lx, 3m: 441 lx, 6m: 119 lx
Luminous flux:	1200 Im rated light flux at 90°
Housing color:	Black matte
Material:	Aluminum casting; metal; plastic
Dimensions:	Length: 19 cm
	Width: 8,5 cm
	Height: 13,5 cm
	Diameter: Ø 6 cm
Weight:	0,44 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	E
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1 m
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm