

## OMNITRONIC DD-4750 USB turntable

Direct drive DJ turntable with USB interface and recording software

Art.n.: 10603020

GTIN: 4026397356076



**L'articolo non è più disponibile.**

### Features :

- Direct drive high-torque motor
- Quartz-controlled for highest speed precision
- Built-in USB port and additional phono preamplifier, for a high-quality and convenient digitization of analog vinyl records
- Plug & play: no driver installation required, unit is identified automatically
- Sampling rates of 44.1 kHz and 48 kHz in stereo, resolution: 16 bits
- Incl. software for recording and editing
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control  $\pm 10\%$ ,  $\pm 20\%$ ,  $\pm 50\%$
- Quick start
- 2 large start/pause buttons
- Selectable quartz-controlled pitch lock
- Motor with reverse run can be switched off
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing feet
- Switchable phono/line output
- Delivery includes pick-up system, slipmat, RCA and USB cable
- USB 1.1 support
- Suitable for Windows XP, Vista, 7 and Mac OS X
- Delivery without dust cover

### Logistica

EAN / GTIN: 4026397356076

Peso : 10,90 kg

Lunghezza : 0.52 m

Larghezza : 0.43 m

Altezza : 0.20 m

## Dati tecnici :

|                              |                                                             |
|------------------------------|-------------------------------------------------------------|
| Alimentazione elettrica:     | 115/230 V AC, 50/60 Hz                                      |
| Potenza totale installata:   | 13,50 W                                                     |
| Intervallo di frequenza:     | 50 - 20000 Hz                                               |
| Misure:                      | Larghezza: 44,9 cm<br>Profondità: 37 cm<br>Altezza: 14,5 cm |
| Peso:                        | 9,80 kg                                                     |
| Type:                        | manual turntable                                            |
| Drive method:                | quartz-controlled direct drive                              |
| Motor:                       | brushless DC motor                                          |
| Turntable platter:           | d=330 mm, aluminum diecast                                  |
| Speed:                       | 33 1/3 RPM, 45 RPM and 78 RPM                               |
| Change time between speeds:  | <0.3 sec                                                    |
| Initial torque:              | >3.5 kg/cm                                                  |
| Start time:                  | <0.3 sec                                                    |
| Brake:                       | electronic brake                                            |
| Stop time:                   | <0.3 sec                                                    |
| Pitch adjustment:            | ±10 %, ±20 %, ±50 %                                         |
| Wow and flutter:             | <0.1 %                                                      |
| Rumble:                      | 55 dB DIN B                                                 |
| Tone arm:                    | S-shape with Cardan's suspension                            |
| Tone arm length:             | 230 mm                                                      |
| Overhang:                    | 15 mm                                                       |
| Anti-skating range:          | 0-4 g                                                       |
| Applicable cartridge weight: | 6-10 g                                                      |
| Stylus pressure range:       | 3-4 g                                                       |
| Phono output level:          | 1.5-3.6 mV/ 1 kHz 5 cm/sec                                  |
| Line output level:           | 90-216 mV/ 1 kHz 5 cm/sec                                   |
| Channel separation:          | >15 dB                                                      |
| Output connectors:           | RCA, USB type B                                             |
| Dimensions:                  | 449 x 370 x 145 mm                                          |