

EUROLITE FSM-150 Smoke machine

Fog machine with variable output angle

Art.n.: 51701967

GTIN: 4026397336917



L'articolo non è più disponibile.

Descrizione :

Fog clouds at its finest!

There is no doubt about the important role fog plays in the entertainment industry. But a fogger is not simply a fogger. Regarding the quality, great differences can be found. Presenting our EUROLITE FSM-150 we now offer you a professional unit, which is definitely no mistake, as it does convince through its outstanding workmanship, construction and power. In huge discotheques or on stages its preferences come into their own. It has a very strong smoke output up to 4 meters at its disposal. To prevent an unintentional after fogging. Moreover an automatic output stop was installed. A very useful characteristic: the variable output angle. With the FSM-150 it can be set approximately 70° upwards or downwards. Thus you can precisely control the fog and set it purposefully. Try it out. This reliable fogger will not leave you out in the rain!

Features :

- Smoke machine with powerful smoke output
- Output angle adjustable by approx. 70° upwards and 70° downwards
- Control via supplied on/off remote control
- Remote control connection via 5-pin DIN socket
- Ideal for large discotheques or large stages
- With mounting bracket for hanging installation
- DMX control via every standard DMX controller
- Portata di uscita: Circa 4 m
- Ampia capacità del serbatoio
- Già pre-programmato con LED PC-Control 512

Logistica

EAN / GTIN: 4026397336917

Peso : 13,80 kg

Lunghezza : 0.66 m

Larghezza : 0.38 m

Altezza : 0.33 m

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	1500 W
Tempo di riscaldamento:	Circa 8 min
Volume di uscita:	Circa 900 m ³ /min
Portata di uscita:	Circa 4 m
Capacità serbatoio:	5 l
Consumo di fluido:	Circa 50 ml/min
Canali DMX:	1
Pre-programmato con:	LED PC-Control 512
Misure:	Larghezza: 35 cm Profondità: 56 cm Altezza: 39 cm
Peso:	12,65 kg
DMX channels:	1
DMX connection:	3-pin XLR
Smoke-output:	4 m
Warm-up time:	8 min.
Fluid consumption:	50 ml/min.
Output volume:	900 m ³ /min.
Tank capacity:	5 l
Dimensions (L x W x H):	560 x 350 x 390 mm