

## ALUTRUSS SINGLELOCK SP-2000 Tubo QUICK-LOCK

Tubo a traversa semplice con connettori QUICK-LOCK

Art.n.: 60210040

GTIN: 4026397187120



**Prezzo di listino: 77.23 €**

incl. 19% IVA

### Descrizione :

SINGLELOCK SP 1-point truss system  
SINGLELOCK SP is a 1-point truss system made of aluminum. The individual elements are connected via one cone, pivots and pins.

The advantage of the conical connection system is that the cone completely fits into the main chord so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The main chord is made of 50 mm aluminum tube with 2 mm wall thickness and offers a good relation between strength and weight.

SINGLELOCK SP is a stable truss system for higher loads and extended durability. This system is mainly designed for intense use in stage installations, fair installations, event installations but also for permanent installations in discotheques and theatres.

With SINGLELOCK SP, decorative frames with advertising signs, transmission canvas etc. can be realized.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

### Logistica

EAN / GTIN: 4026397187120

Peso : 1,85 kg

Lunghezza : 2.00 m

Larghezza : 0.05 m

Altezza : 0.05 m

Merci voluminose

## Features :

---

- Peso leggero
- Per la decorazione o la realizzazione di telai per pellicole di proiezione
- Montaggio facile
- Tubo della cinghia: 50 mm
- Made in Europe
- Per campi di applicazione come, ad esempio.: Allestimento negozi; allestimento di fiere; centri sportivipalestre; palco; noleggiatore
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

### **Dotazione della fornitura**

- 1 x set di connettori

## Dati tecnici :

---

Struttura:	Montaggio facile
Tubo della cinghia:	50 mm x 2 mm
Processo di saldatura:	Impulso TIG
Materiale di saldatura:	AlMg 5
Colore:	Color alluminio
Misure:	Lunghezza: 200 cm
Peso:	1,85 kg